



CLEAN ROOM GRID 24mm Grid System

BENEFITS

- Factory-finished high performance gasket between grid flange and ceiling tiles provides robust sealing.
- PVC Hold Down Clip option to comply with non-ferrous application.
- Stainless steel XL staked-on end detail of cross tee provides clean and secure locked connection.
- High quality aluminum alloy inhibits red rusting, and can be used in nonmagnetic environment.
- System is engineered and designed to coordinate with Armstrong & Thermatex ceilings.

Material

High quality extruded aluminum alloy

Surface Finish

Powder coating

Cross Tee/ Main Beam

Interface

Flush joint

End Detail

Main beam: Joiner

Cross Tee: Staked-on clip

Classification









Light duty LD

Colour Selection

White (WH)

CLEAN ROOM GRID

24mm Grid System

Clean Room Grid						
	Item Number	Description	Dimensions			
			Rout Spacing	Length	Height	Width
	BP454032*	3600mm Main Beam	300mm	3600mm	38mm	24mm
	BP453032	1200mm Cross Tee	600mm	1200mm	38mm	24mm
	BP452032	600mm Cross Tee	-	600mm	38mm	24mm
Angle Molding						
	BPT1925HAC	3600mm Angle Molding	-	3600mm	25mm	19mm
Accessories						
	BP4501	PVC hold down clip for lay-in board	-	29mm	19mm	10mm
	BP4502	PVC hold down clip for tegular board	-	38mm	19mm	10mm
 Sustainability	 25%					

Note: Hanger Spacing 1200mm, Load: * 11.4kg/m

Contact

For further details, please contact your local representative or email asia.support@knaufarmstrong.com