

CORRIDOR

FREE-SPANNING, DEMOUNTABLE ACOUSTICAL CEILING

- ✓ Exceptionally fast and easy installation
- ✓ Simple ceiling planning
- ✓ Easy access to installations
- ✓ Ideal for corridors and narrow rooms
- ✓ Sustainable






FEATURES

- Self-supporting ceiling
- Free span up to 2.4 m
- No suspension grid required
- Rectangular tiles

SUSTAINABLE PRODUCT:

- Made of gypsum
- Safe material
- 100% recyclable
- Improved indoor climate
- Repaintable without loss of acoustics

PRODUCT VARIANTS

EDGE DESIGN	<div></div> <div>EDGE D</div> <div>(rebated and grooved edge)</div> <div>Free-spanning tile with visible trim at short ends</div>				
PERFORATION DESIGN	<div></div>	<div></div>	<div></div>	<div></div>	
Also available without perforations (Regula)					
PERFORATION MEASURES	<div>MICRO</div> <div>Square 3×3 mm</div> <div>c/c 8.33 mm</div>	<div>GLOBE</div> <div>Circles Ø 6 mm</div> <div>c/c 15 mm</div>	<div>QUADRIL</div> <div>Square 12x12 mm</div> <div>c/c 30 mm</div>	<div>TANGENT</div> <div>Obround 4x14 mm</div> <div>c/c 10/20 mm</div>	
PERFORATION %	10.6%	10.6%	14.2%	21.3%	
NRC, @ 200mm, no mineral wool	0.60	0.65	0.65	0.75	
NRC, @ 200mm, 50mm mineral wool	0.75	0.70	0.80	0.95	
ALPHA-W, @ 200mm, no mineral wool	0.65	0.60	0.60	0.80	
ALPHA-W, @ 200mm, 50mm mineral wool	0.75	0.65	0.75	0.95	
LIGHT REFLECTION	72.1%	72.8%	75.1%	70.9%	
SIZES, mm	Standard	400 x 1200 / 1800 / 2400 x 9.5			-
	Other options	300 x 1200 - 2400 x 9.5 400 x 1200 - 2400 x 9.5			
TILE WEIGHT, kg/m²	11.66 - 12.69 kg/m²				
SURFACE TREATMENT	Front: White acrylic paint, RAL 9003, gloss 5. Back: Acoustic felt backing. Available in other colours on request.				
	Also available with hygienic Medifend surface paint on request. Medifend has antibacterial and fungistatic effect. Tested in accordance with DIN ISO 846, method B and B'.				
SYSTEM COMPONENTS	1) Gypsum ceiling tile, 2) Flex runner, 3) Wall angle, 4) Hangers				
CERTIFICATES	1) Environmental product declaration, 2) FDES – life cycle analysis, 3) Danish Indoor Climate Labelling, 4) ISO 16000-9 Emission of VOCs, 5) UL-listed in accordance to R26164				

PRODUCT PERFORMANCE

FIRE RATING

A2-s1, d0

AIR QUALITY

Indoor value: 10 days
Particle emission: LOW
Active air purification with
Cleaneo technology

FOR INTERIOR APPLICATION ONLY

LOAD-BEARING CAPACITY

Up to 3 kg pr. tile (at max. 2mm
deflection)

ROBUSTNESS

Glass fibre reinforced gypsum. High
pressure resistance. Highly stable
ceiling ensured by tile density.