



## ARMSTRONG METALWORKS™ LAY-IN

- Available in a variety of edge details for installation on Prelude 24mm, Suprafine or Silhouette 15mm suspension system
- Diversity of design and application
- Easily assembled and fully demountable
- Cost effective ceiling solution
- Tiles are easily lifted out by hand, allowing full and easy access to the ceiling void

Panel Options	Board	Tegular 8	Microlook 8	
<b>Edge details</b>	 24mm Exposed Grid	 24mm Exposed Grid	 15mm Exposed Grid	
<b>Material</b>	Galvanized Steel (Aluminum optional)			
<b>Patterns</b> *Perforated panels feature an unperforated border and include acoustical fleece.	 Non Perforated (M1)	 Micro Perforated (M2) 1.5mm Ø 19% Open Area	 Micro Perforated (M9) 1.5mm Ø 9.5% Open Area	 Standard Perforated (M10) 2.5mm Ø 16% Open Area
<b>Dimensions (mm)</b>	600 x 600 1200 x 600 (Other sizes available on request)			
<b>Suspension System</b>	Standard Peakform Prelude 24mm or Suprafine 15mm Suspension System			
<b>Weight</b>	4.6 kg/m <sup>2</sup>			
<b>Colour</b>	Polyester Powder Coated – Global White                      Wood Effects Available by Request			
<b>Sound absorption</b>	NRC 0.70 (M2) / NRC 0.75 (M9) / NRC 0.80 (M10) - Perforated Option with fleece, without additional infill. Contact your local sales representative for test data.			
<b>Sound attenuation</b>	Approximately 18 dB (without additional infill). <b>Optional:</b> High Attenuation Performance Up to 38dB (NRC 0.60) with additional mineral infill.			
<b>Fire reaction</b>	CLASS 0/1 based on BS 476 Part 6 & 7			
<b>Handling</b>	100% upward demountable without tooling.			
<b>Durability</b>				
<b>Cleanability</b>				

All sizes are nominal. Product availability may vary.

## Contact

For further details, please contact your local representative or email [asia.support@knaufarmstrong.com](mailto:asia.support@knaufarmstrong.com)